



IDentity 4100 ETSI

Ultra High Frequency 865 - 868 MHz

High-Performance Reader for Supply Chain Logistics and Automatic Vehicle Identification Applications

Overview

The Sirit IDentity 4100 is designed for use in Supply Chain Logistics and Vehicle Parking and Access Control applications. It was designed to withstand harsh environments associated with outdoor and warehouse use.

The IDentity 4100 consists of a weather resistant enclosure containing both the RFID reader and circularly polarized antenna. The IDentity 4100 has an external antenna port that can be used to add one additional read point.

The IDentity 4100 can serve a wide variety of applications. Use-cases range from Supply Chain Logistics (SCL) including portals, and asset tracking to Parking and Access Control (PACS) applications.

The weather resistant enclosure and circularly polarized antenna have been designed to survive the most demanding weather, temperatures and humidity requirements while delivering optimal performance in Europe and all ETSI regulatory markets.




Identity 4100 ETSI

High-Performance, Multi-Protocol Reader



Specifications

Frequency:	UHF 865-868 MHz
Supported Protocols:	EPC Gen 2, ISO18000-6C protocols. Additional protocols may be supported through license upgrades.
Operating Modes:	Single Read Point Mode Dual Read Point Mode (with external antenna)
Communications:	10/100 Ethernet Port
RF Power:	10 mW - 724 mW conducted (+28.6 dBm)
Input Power:	12 to 24 Vdc
Power Consumption:	13W at idle; 36W typical at 1.2W RF; 40W max at 1.2W RF
Connections:	RS-232, Digital I/O, Ethernet LAN; also 1 - RP-TNC (reverse polarity) for external antenna connection
Upgradeable Firmware:	Yes
Operating Temperature:	-40°C to 55°C (-40°F to 131°F)
Storage Temperature:	-40°C to 85°C (-40°F to 185°F)
Relative Humidity:	100%, condensing
Dimensions (LxWxD):	30.5 x 30.5 x 10.2 cm (12 x 12 x 4.0 in.)
Weight:	~4.8 kg (10.5 lbs)
Regulatory:	Compliant to ETSI EN 302 208
Case Material:	Aluminum cast, IP65 rated



SIRIT - CANADA
372 Bay Street, Suite 1100
Toronto, Ontario M5H 2W9 Canada
Tel: 416.367.1897
Fax: 416.367.1435

SIRIT - USA
1321 Valwood Parkway, Suite 620
Carrollton, Texas 75006 USA
Tel: 972.243.7208
Fax: 972.243.8034

901 Lane Avenue, Suite 100
Chula Vista, California 91914 USA
Tel: 619.656.2515
Fax: 619.872-0662

For more information,
contact sales toll free
at 1.866.338.9586

E-mail: sales@sirit.com



About Sirit Inc.

Sirit Inc. (TSX: SI) is a leading provider of Radio Frequency Identification (RFID) reader technology to OEMs and solution providers worldwide. Harnessing the power of Sirit's enabling-RFID technology, customers are able to more rapidly bring high quality RFID solutions to the market with reduced initial engineering costs. Sirit's products are built on more than 15 years of RF domain expertise addressing multiple frequencies (LF/HF/UHF), multiple protocols and are compliant with global standards. Sirit's broad portfolio of products and capabilities are easily customized to address new and traditional RFID market applications including Supply Chain & Logistics, Cashless Payment, Access Control, Automatic Vehicle Identification, Inventory Control & Management, Asset Tracking and Product Authentication. For more information, visit www.sirit.com.



The "RFID by Sirit" symbol signifies that Sirit Inc.'s high quality RFID reader technology resides within this product.

© 2008 Sirit Inc., all rights reserved. "Sirit", the Sirit Design, "RFID by Sirit", the RFID by Sirit Design and "vision beyond sight" are all trademarks of Sirit Inc. All other trademarks are the property of their respective owners. Specifications subject to change without notice.