

INfinity 9320



MULTI-PROTOCOL

- EPC Gen 2
- ISO 18000-6A, 6B
- UCode 1.19
- Class 1
- Class 0, 0+

MULTI-REGIONAL

- MP9320 v2.8 (FCC)
- MP9320 v2.8e (ETSI)

Highest rated reader flexibility and configurability

New user-friendly RAPID API and RF Command Suite



INfinity 9320 v2.8

Ultra High Frequency 902 - 928 MHz
High Performance Multi-Protocol Reader Module

EPC Gen 2 Ready

The INfinity 9320 v2.8 reader extends its acclaimed multi-protocol capability by adding support for EPC Gen 2 tags. The full complement of mandatory and optional Gen 2 features is provided, making it fully interoperable with mixed populations of Gen 2 and legacy UHF tags.

Robust RFID Network Performance

The DSP-based software-defined architecture of the IN9320 v2.8 reader offers a number of feature and performance enhancements designed for high performance RFID network operation including:

- Support for mixed RFID tag protocol operation including EPC Gen 2, Class 1, 0, 0+, ISO 18000-6A/B and UCode 1.19 tags;
- Regulatory compliance for use in multi-regional regulatory markets (IN9320 v2.8 for North America, v2.8e for European and Asian markets);
- Configurable read/write power settings on each of its four antenna ports makes the INfinity 9320 v2.8 reader well suited for loading dock portals, conveyors, tagging stations, and other UHF RFID applications.

Easy-to-Use, Easy-to-Integrate

The Microsoft Windows™-based RF Command Suite (RFCS) program makes it easier than ever to configure the reader for each application.

RAPID (RFID Applications Programming Interface for Developers) is a new API that simplifies enterprise application integration of Sirit RFID readers using familiar Java and Microsoft .NET programming environments.

A full complement of network connections are provided including serial RS-232, RS-485, and 10/100 Mbps Ethernet.

And the INfinity 9320 v2.8 is software upgradable to ensure it always stays current with the latest feature offerings.

INfinity 9320 v2.8

902 - 928 MHz RFID Reader Module



Performance Characteristics

EPC Gen 2 ready	Provides Gen 2 operational feature set including all mandatory for reading and writing to Gen 2 tags and optional commands
Multi-protocol operation	Supports multiple tag protocols concurrently (Gen 2, Class 1, 0, 0+, ISO18000-6A, 6B, UCode 1.19 -0 simultaneously or individually)
DSP-based software architecture	Enhanced system performance, improved read and write speeds
Four (4) TX/RX antenna ports with individually adjustable power settings and sensitivity	Well suited for loading dock portal and conveyor applications
Multi-regional regulatory compliance:	Compliant with North American (FCC) regulatory requirements (IN9320 v2.8e for European and Asian compliance)
Full network connectivity	RS-232, RS-485, 10/100 Mbps Ethernet connections
Four (4) digital input / four (4) digital output lines	Integrated ability to sense external triggers and control actuators enhances performance in multi-reader environments
Unique label applicator features	Gated tag operation, write/verify, dynamic power boost features for high speed label applicators
RF Command Suite	Easy to set up using MS Windows-based configurator
RAPID API	New API makes enterprise applications integration capability easy using Java and Microsoft .NET development platforms
Firmware upgradeable	Keeps the reader current with latest firmware updates

Specifications

Frequency	902-928 MHz
RF Power	4W EIRP
Antenna	Four SMA connectors
Electrical Power	15 Vdc, 3A
Power Supply	110-240 VAC Input
Communication Ports	RS-232, RS-485, 10/100 Mbps Ethernet
Digital Input/Output	Four digital input lines, four digital output lines
Case Material	Aluminum
Dimensions	5 in x 7 in x 9.5 in (127 mm x 178 mm x 241 mm)
Weight	(4 lbs.) 1.8 kg
Operating Temperature	-4° F to 104° F (-20° C to 40° C)
Operating Humidity	5-95% relative, noncondensing
Storage Temperature	-40° F to 185° F (-40° C to 85° C)
Mounting	Horizontal or vertical orientation
Regulatory Compliance	FCC Part 15

About Sirit Inc.

Sirit Inc. (TSX: SI) is a leading provider of Radio Frequency Identification (RFID) reader technology to OEMs and solution providers worldwide. Harnessing the power of Sirit's enabling-RFID technology, customers are able to more rapidly bring high quality RFID solutions to the market with reduced initial engineering costs. Sirit's products are built on more than 12 years of RF domain expertise addressing multiple frequencies (LF/HF/UHF), multiple protocols and are compliant with global standards. Sirit's broad portfolio of products and capabilities are easily customized to address new and traditional RFID market applications including Supply Chain & Logistics, Cashless Payment, Access Control, Automatic Vehicle Identification, Inventory Control & Management, Asset Tracking and Product Authentication. For more information, visit www.sirit.com.

SIRIT - CANADA
372 Bay Street, Suite 1100
Toronto, ON M5H 2W9 Canada
Tel: 416.367.1897
Fax: 416.367.1435

SIRIT - USA
1321 Valwood Parkway, Suite 620
Carrollton, Texas 75006 USA
Tel: 972.243.7208
Fax: 972.243.8034

2525 Meridian Parkway, Suite 60
Durham, North Carolina 27713 USA
Tel: 919.281.1541
Fax: 919.281.1551

9815 Cogdill Road, Suite 4
Knoxville, Tennessee 37932 USA
Tel: 865.966.8775
Fax: 865.966.8812

For more information,
contact sales toll free
at 1.866.338.9586

E-mail: rfd@sirit.com


www.sirit.com



The "RFID by Sirit" symbol signifies that Sirit Inc.'s high quality RFID reader technology resides within this product.

© 2006 Sirit Inc., all rights reserved. "Sirit", the Sirit Design, "RFID by Sirit", the RFID by Sirit Design and "vision beyond sight" are all trademarks of Sirit Inc. All other trademarks are the property of their respective owners. Specifications subject to change without notice.