

FEATURES

- Integrated reader/antenna
Designed for operation with UHF tags yielding superior read range when compared to traditional long range proximity card systems
- Stand-alone operation
Storage of tag list in reader using IDentity MaX firmware enables stand-alone functionality
- Ethernet capability
Allows network access through standard Ethernet connectivity and Power over Ethernet (PoE) functionality

IDentity MaX Reader

Integrated Automatic Vehicle Identification (AVI) Reader
ETSI Compliant, Ultra High Frequency (UHF) 865-868 MHz

Overview

Sirit's IDentity MaX reader uses UHF radio frequency identification (RFID) technology to create an integrated automatic vehicle identification (AVI) system offering superior price/performance characteristics over traditional long range proximity card systems. Protected against the elements by a weather resistant enclosure, this self-contained combination reader and antenna unit is intended as a single read point in a pedestal, pole, wall or ceiling mounted configuration. The integrated reader provides an economical solution for automatic vehicle identification and access control applications alike.

The IDentity MaX reader supports four independent discrete TTL capable inputs, which may be used for vehicle detecting loops, light curtains or other detection schemes required by the installation. Additionally, the reader has four discrete 5V outputs which are current limited and electronically configurable for either push pull or external pull up resistors.

. These outputs can be used for gate vending control, vehicle stop-and-go light control or other purposes. Sirit has optional relay modules for applications that require output voltages greater than 5V.

Communication


The IDentity MaX system communicates transponder activity to a variety of established host systems via RS-232, RS-422, RS-485, or Wiegand protocols.



Identity MaX Reader

865 - 868 MHz Integrated Access Control Reader



Performance Characteristics		
Frequency:	ETSI UHF band, 865 MHz to 868 MHz	
Tag Protocols Supported:	All Sirit Identity MaX tags based on industry standard UHF protocols	
Working Range:	Read performance varies based on tag and reader configuration and environment.	
Antenna Type:	Circular polarized	
Communications Protocol:	Wiegand, RS-232, RS-422, RS-485, USB 2.0. 802.3af Power over Ethernet. The serial interfaces support baud rates of up to 115 Kbps	
Data Format:	Configurable 26 to 34-bit (Wiegand); future support for higher Wiegand configuration up to 154-bit	
External Inputs:	Four	
External Outputs:	Four	
Ethernet Compatible	Yes	
Translation Table:	Yes	
Tag Buffering:	Yes	
LED	Yes	
Stand Alone Operation	Supported	
Physical Characteristics		
Dimensions (LxWxD):	~30.5 x 25.4 x 10.2 cm (12.00 x 10.00 x 4.00 in.)	
Packaging:	Weather proof integrated antenna enclosure	
Mounting:	Pedestal, pole, wall or ceiling mounted	
Weight:	~5.4 kg (~12 lb.)	
Environment		
Operating Temperature:	-25°C to +60°C (-13°F to 140°F)	
Storage Temperature:	-40°C to +114°C (-40°F to 237°F)	
Relative Humidity:	85% non-condensing	
Power:	Power over Ethernet (+48VDC, 600 mA) or 85 to 264 VAC, 600mA	
Regulatory:	ETSI EN302-208-1	
Ordering Information:		
Part Number:	Description:	
IDMAX-E-READER	MaX Reader (ETSI version)	
IDMAX-CABLE-20	20 ft., 30 pin cable with pre-assembled cannon plug	
IDMAX - CMB	Ceiling mount bracket	
IDMAX - WMB	Pole/wall mount bracket	
IDMAX - PMB	Pedestal mount bracket	
IDMAX-MAN-H/W	Hardware installation manual	
IDMAX-REL-01	Relay kit with one relay	

SIRIT - CANADA
 372 Bay Street, Suite 1100
 Toronto, ON M5H 2W9 Canada
 Tel: 416.367.1897
 Fax: 416.367.1435

SIRIT - USA
 1321 Valwood Parkway, Suite 620
 Carrollton, Texas 75006 USA
 Tel: 972.243.7208
 Fax: 972.243.8034

For more information,
 contact sales toll free
 at 1.800.498.8760

E-mail: max@sirit.com

www.sirit.com

About Sirit Inc.

Sirit Inc. (TSX: SI) is a leading provider of Radio Frequency Identification (RFID) reader technology to OEMs and solution providers worldwide. Harnessing the power of Sirit's enabling-RFID technology, customers are able to more rapidly bring high quality RFID solutions to the market with reduced initial engineering costs. Sirit's products are built on more than 13 years of RF domain expertise addressing multiple frequencies (LF/HF/UHF), multiple protocols and are compliant with global standards. Sirit's broad portfolio of products and capabilities are easily customized to address new and traditional RFID market applications including Supply Chain & Logistics, Cashless Payment, Access Control, Automatic Vehicle Identification, Inventory Control & Management, Asset Tracking and Product Authentication. For more information, visit www.sirit.com.



The "RFID by Sirit" symbol signifies that Sirit Inc.'s high quality RFID reader technology resides within this product.

© 2007 Sirit Inc., all rights reserved. "Sirit", the Sirit Design, "RFID by Sirit", the RFID by Sirit Design and "vision beyond sight" are all trademarks of Sirit Inc. All other trademarks are the property of their respective owners. Specifications subject to change without notice.